



# Product Information Sheet

## HALOTRON



Halotron is a clean, non-conductive gaseous agent that is an excellent replacement for Halon 1211 extinguishers. Halotron is suitable for use on Class A, Class B and Class C fires.

**TYPICAL USES:** For protecting sensitive electronic equipment in offices, classrooms, churches, parking garages, and hotel/motel assembly halls and guest areas. For protecting sensitive electronic equipment in businesses such as retail stores, light manufacturing facilities, research facilities, auto dealerships, vehicle/aircraft/marine service centers, and manufacturing processes such as painting, dipping, and coating.

Not UL Listed or suitable for use on fires involving cooking oil and grease. Recommended for use on sensitive electronic equipment.



LISTED

USCG  
Approved

DOT  
Compliant

| Model              | 2.5F               | 2.5F V/B           | 2.5H              | 2.5H V/B          | 5F                  | 5F V/B              | 5H                  | 5H V/B              | 11                 | 15                   |
|--------------------|--------------------|--------------------|-------------------|-------------------|---------------------|---------------------|---------------------|---------------------|--------------------|----------------------|
| Pt. # ALUM. VALVE  | 70258              | 70251              | 70259             | 70256             | 70510               | 70550               | 75550               | 75555               | 71100              | 71550                |
| Pt. # BRASS VALVE  | N/A                | N/A                | N/A               | N/A               | 70511               | 70551               | 75551               | 75556               | 71101              | 71551                |
| AGENT CAPACITY     | 2.5 lb. (1.13 kg)  | 2.5 lb. (1.13 kg)  | 2.5 lb. (1.13 kg) | 2.5 lb. (1.13 kg) | 5 lb. (2.27 kg)     | 5 lb. (2.27 kg)     | 5.5 lb. (2.49 kg)   | 5.5 lb. (2.49 kg)   | 11 lb. (5 kg)      | 15.5 lb. (7.03 kg)   |
| UL RATING          | 2-B:C              | 2-B:C              | 2-B:C             | 2-B:C             | 5-B:C               | 5-B:C               | 5-B:C               | 5-B:C               | 1-A:10-B:C         | 2-A:10-B:C           |
| DISCHARGE TIME     | 9 sec              | 9 sec              | 9 sec             | 9 sec             | 9 sec               | 9 sec               | 9 sec               | 9 sec               | 9 sec              | 13 sec               |
| RANGE (FT/M)       | 6-10 / 1.8-3       | 6-10 / 1.8-3       | 6-10 / 1.8-3      | 6-10 / 1.8-3      | 9-15 / 2.7-4.5      | 9-15 / 2.7-4.5      | 9-15 / 2.7-4.5      | 9-15 / 2.7-4.5      | 9-15 / 2.7-4.5     | 12-18 / 3.7-5.5      |
| OPERATING PRESSURE | 100 psi (689 kPa)  | 100 psi (689 kPa)  | 100 psi (689 kPa) | 100 psi (689 kPa) | 100 psi (689 kPa)   | 100 psi (689 kPa)   | 100 psi (689 kPa)   | 100 psi (689 kPa)   | 100 psi (689 kPa)  | 125 psi (862 kPa)    |
| BRACKET            | Wall               | Vehicle            | Wall              | Vehicle           | Wall                | Vehicle             | Wall                | Vehicle             | Wall               | Wall                 |
| USCG APPROVAL      | N/A                | N/A                | N/A               | N/A               | Type B:C Size I     | Type B:C Size I     | Type B:C Size I     | Type B:C Size I     | Type B:C Size I    | Type B:C Size II     |
| SHIP WEIGHT        | 5.25 lb. (2.4 kg)  | 5.5 lb. (2.49 kg)  | 5.5 lb. (2.49 kg) | 5.75 lb. (2.6 kg) | 9.25 lb. (4.2 kg)   | 9.5 lb. (4.3 kg)    | 10.0 lb. (4.5 kg)   | 10.25 lb. (4.7 kg)  | 21.25 lb. (9.6 kg) | 25.75 lb. (11.75 kg) |
| UNIT HEIGHT        | 13.375 in (34 cm)  | 13.375 in (34 cm)  | 13.375 in (34 cm) | 13.375 in (34 cm) | 16.375 in (41.6 cm) | 16.375 in (41.6 cm) | 16.375 in (41.6 cm) | 16.375 in (41.6 cm) | 17.5 in (44.5 cm)  | 17.5 in (44.5 cm)    |
| UNIT WIDTH         | 5.625 in (14.3 cm) | 5.625 in (14.3 cm) | 6.75 in (17.1 cm) | 6.75 in (17.1 cm) | 6.5 in (16.5 cm)    | 7.25 in (18.5 cm)   | 6.5 in (16.5 cm)    | 7.25 in (18.5 cm)   | 8.625 in (21.9 cm) | 8.625 in (21.9 cm)   |
| UNIT DIAMETER      | 3.375 in (8.6 cm)  | 3.375 in (8.6 cm)  | 3.375 in (8.6 cm) | 4.25 in (10.8 cm) | 4.25 in (10.8 cm)   | 4.25 in (10.8 cm)   | 4.25 in (10.8 cm)   | 4.25 in (10.8 cm)   | 7 in (17.8 cm)     | 7 in (17.8 cm)       |